

SPECIFICATION

SERIES 15/G-SP

PROBE P15/G-SP

MECHANICAL
 Full travel: 4.4mm
 Recommended working travel: 3.5mm

SPRING FORCE
 Preload: 0.4N 0.6N
 @ Working travel: 1.5N 3.0N
ORDER PART NO. -1 -2

Other springs available on request

RECEPTACLES

RECEPTACLES

R15/G-S

TIP STYLE

P15/G-Dx

TYPE

SP

STEEL / BeCu

ORDER PART NO	TIP DIAMETER "A"	COLLAR DIAMETER "B"	TIP LENGTH "C"	OAL LENGTH "D"
P15/G-D1-x-SP	0.65	1.5	4.0	29.9
P15/G-D2-x-SP	0.65	1.5	2.8	28.7

SPECIFICATION

SERIES 60/G-SP

PROBE P60/G-SP

MECHANICAL
 Full travel: 5mm
 Recommended working travel: 4mm

SPRING FORCE
 Preload: 0.5N 0.5N
 @ Working travel: 1.5N 3.0N
ORDER PART NO. -1 -2

Other springs available on request

TIP STYLES

P60/G-Dx P60/G-Fx

TYPES

SP SP3

STEEL / BeCu STEEL / BeCu

ORDER PART NO	TIP DIAMETER "A"	COLLAR DIAMETER "B"	TIP LENGTH "C"	OAL LENGTH "D"
P60/G-D1-x-SP	1.0	3.5	2.8	29.3
P60/G-D2-x-SP	1.0	3.5	4.0	30.5
P60/G-D3-x-SP	1.4	3.5	2.4	28.9
P60/G-D4-x-SP	1.4	3.5	3.3	29.8
P60/G-D5-x-SP	1.4	3.5	4.0	30.5
P60/G-F1-x-SP or SP3	1.3	4.7	2.7	29.2
P60/G-F2-x-SP or SP3	1.3	4.7	3.6	30.1
P60/G-F3-x-SP or SP3	1.3	4.7	5.3	31.8
P60/G-F4-x-SP	1.4	3.5	1.7	28.2
P60/G-F5-x-SP	1.4	3.5	2.0	28.5
P60/G-F6-x-SP	1.4	3.5	3.0	29.5
P60/G-F7-x-SP or SP3	1.8	4.5	1.5	28.0
P60/G-F8-x-SP	2.3	3.5	1.8	28.3
P60/G-F9-x-SP	2.3	3.5	2.0	28.5
P60/G-F10-x-SP or SP3	4.0	5.0	2.0	28.5

Other sizes available on request for both types.

Note: SP3 requires special tool

RECEPTACLES

RECEPTACLES

R60/G-S R60/G-KS

PROBE ORDER CODE
P60/G - Dx-X - SP or SP3
 Series Tip Style Spring Type