

P201/G screw-in switch probes with the thread at the BOTTOM of the probe barrel. P201/G min centres 4.0mm switch travel 1.7mm
A slotted head version of P201/G allows fitting/removal with a screwdriver.

BOTTOM THREAD

SPECIFICATION

SERIES 201/G

PROBE P201/G

STANDARD FORM **LONG FORM**

Recommended minimum centres: 4.0mm

MECHANICAL
Full travel: 5.0mm
Recommended working travel: 4.0mm
Switch travel: 1.7mm

SPRING FORCE
Preload: 0.25N 0.4N 0.6N 1.4N 2.0N
@ Working travel: 1.25N 2.3N 3.5N 7.0N 10.0N
Switch travel: 0.45N 1.0N 1.6N 3.6N 5.2N

ORDER PART NO. -0 -1 -2 -3 -4

ELECTRICAL
Max current: 1 amp
Terminal resistance: <25m ohms
Insulation voltage: 1KV
Recommended hole size: 3.5mm

TIP STYLES

P201/G-A **P201/G-AL/AL1** **P201/G-C/C4/C6**

LONG FORM

STEEL / BeCu STEEL / BeCu STEEL / BeCu

<p>P201/G-C1</p> <p>STEEL / BeCu</p>	<p>P201/G-C2/C7/C8/C9</p> <p>BeCu</p>	<p>P201/G-CL/CL6/CL8</p> <p>STEEL / BeCu</p>	<p>P201/G-CL1</p> <p>STEEL / BeCu</p>	<p>P201/G-CL2</p> <p>STEEL / BeCu</p>	<p>P201/G-FO/F3</p> <p>STEEL / BeCu</p>	<p>P201/G-F/F1</p> <p>STEEL / BeCu</p>
<p>P201/G-F1/F2/F4-POM</p> <p>NYLON</p>	<p>P201/G-FL</p> <p>BeCu</p>	<p>P201/G-FL3</p> <p>BeCu</p>	<p>P201/G-K</p> <p>STEEL</p>	<p>P201/G-FS1/F2/F4</p> <p>BeCu</p>	<p>P201/G-F5/F6/F7/F8</p> <p>BeCu</p>	<p>P201/G-FS1/F5/F6/F7/F8-POM</p> <p>NYLON</p>

RECEPTACLES

R201/G-K **R201/G-5K** **R201/G-KB**

Solder free replacement and height adjustment

P201/G-FL1/FL5 **P201/G-FL6/FL8** **P201/G-FL1/FL3/FL5-POM**

LONG FORM

BeCu BeCu NYLON

PROBE ORDER CODE
P201/G - A - 1
Series Tipstyle Spring Force

Note: Tip Material shown Black - Standard Stock Item Blue - Optional On Request Purple = Minimum order quantity